

9,000 Limited Pro Stock

All Tractors have to meet NTPA/PPL/Outlaw safety standards and chassis configurations. No component chassis allowed.

1. 640 CID and below
 - a. 3 X 4 turbo maximum
 - b. A compressor measurement to be measured at the face of the inlet and must protrude into the intake housing a minimum of 1/8 inch. Map width enhancement grooves allowed. NO SLUGGED DOWN TURBOS ALLOWED. Intercoolers allowed.
 - c. Bosch P-series pump Model 7100 maximum, 16mm barrel limit.
 - d. Weight 9500 Lb.
2. 540 CID and below (Full Pull Productions and Interstate Pullers)
 - a. No turbo limit.
 - b. Bosch A-series pump
 - c. Weight 9200 Lb.
3. 540 CID and Below
 - a. 4.1 turbocharger of any make and model. Billet intake and exhaust wheels allowed.
 - b. Bosch P-series Model 7100 maximum, 16mm barrel limit.
 - c. Weight 9,000 Lb.
4. 540 CID and below
 - a. No turbo limit.
 - b. Bosch P-series Model 7100 maximum 16mm barrel limit.
 - c. Weight 8700 Lb.
 - d. Limited Pro stocks can also compete at this weight.
5. Light Pro 540 ci (+1%) or smaller engine-
 - a. Maximum fuel injection pump Bosch P pump 3000 or 7100 series\
 - b. No billet pumps
6. Limited Pro larger than 540 ci up to 640 ci (+1%) engine-
 - a. Maximum fuel injection Bosch P pump
 - b. No biller pumps
 - c. 4.1 inch intake turbo smooth bore housing (Mo Map Ring) (Use PPL Limited Rule)
 - d. No exhaust restrictions.