Small Tire Tractor Rules

- 1. Weight Class will be 5500.
- 2. Drawbar height of maximum of 20" and minimum of 18" from the center of the axle
- 3. Drawbars are to be stationary in all directions. Turnbuckles to not be above the center of the axle.
- 4. Drawbar to be 1 inch thick, 4 diameter hole no more than 1 ½ in from back edge.
- 5. Tire size will be 15.5.38 or 16.9.34 any cut.
- 6. Length of tractor not to exceed 11ft from the center of the rear axle to the front of the furthest point. No weights beyond rear tires
- 7. No governor strings or wires permitted, 3000 RPM limit.
- 8. Engine fans must be shrouded.
- 9. Exhaust must discharge upward above the highest point.
- 10. One barrel up draft carburetor only. No turbo charger.
- 11. One attempt will be given for changing gears or weights within 75 feet from the start.
- 12. Any parts/weights falling off the tractor onto the track disqualifies the hook.
- 13. Driver must be seated at all times while pulling.
- 14. All pulls are to be started from a tight hitch. No Jerking.
- 15. Tractors must stay within boundaries or they will be disqualified.
- 16. No pressurized tanks, with the exception of LP gas
- 17. Rules of pull are subject to change by the tractor pulling officials.
- 18. All tractors to be weighed before the start of the class parked in the staging area.